

COLOR COATING INSTRUCTIONS

FSorb can be sprayed with an acoustical coating, tinted to a designer color.

FSorb recommends the use of ProCoat's ProCoustic acoustical coating system as supplied by:

ProCoat® Products, Inc.
260 Centre Street, Suite D
Holbrook, MA 02343
Phone (781) 767-2270
Fax (781) 767-2271
info@procoat.com

ProCoustic can be tinted to any color match by your local paint store following their instructions. ProCoat offers "Guidelines for Tinting ProCoustic" that will help you choose the proper base paint to purchase and the tinting guidelines for your local paint store or directly from ProCoat.

ProCoustic can be applied to FSorb as described in ProCoat's "Application Guide" for a spray applied application. Test apply a sample to ensure proper coverage and color consistency.

FSorb can be color coated prior to installation or after installation.

FSorb color coated products should be installed only in areas where direct contact is minimal. If the applied finish on the F-Sorb is damaged, the panel should be completely recoated to provide a consistent finish.

FSorb has a limited One Year Warranty. This warranty covers defects in structural integrity of the panels. If color coated according to the guidelines above and as recommended by ProCoat, the warranty will be maintained. This warranty does not cover damage caused by fire, water, accident, or by any form of abuse except normal wear and tear. The use of unapproved paint systems will void the warranty.

